

CCs' size increases. This behavior was already reported in their original paper. Contrasting these results, the throughput of our algorithm increases, if the CCs size increases. An exception to this behavior is the CC size one, where our algorithm does not extract any CS. So, our algorithm performs better, if the processed data consists of less contour-segments.

V. CONCLUSION

We have presented a parallel algorithm to solve 2d-image-data CCL problems in linear overall complexity. Similar to contour-tracing approaches, the extracted object-contours may also be helpful for certain applications like 2d-object recognition. Our current OpenCL-implementation performs comparable to the fastest previous approaches, when executed on a GPU, if a sufficiently high resolution is applied. Additionally, it scales superior with respect to the data-resolution in case of the tested data-set.

VI. FUTURE WORK

First and foremost, we will research alternatives to the fill contour sub-algorithm, since it limits the asymptotic running-time due to the small number of processors utilizable, when compared to our other sub-algorithms. Perhaps a per-column unification of linked-lists is a better idea. However, these would have to be re-arranged at first in order to solve problems regarding nested connected-components.

Besides, we will improve our implementation. One problem identified is the amount of OpenCL kernel calls (hundreds per processed image). And another one is the limited use of a GPU's local memory provided by OpenCL.

REFERENCES

- [1] A. Rosenfeld, "Connectivity in digital pictures," *J. ACM*, vol. 17, no. 1, pp. 146–160, Jan. 1970. [Online]. Available: <http://doi.acm.org/10.1145/321556.321570>
- [2] J. H. Kim, K. K. Kim, and C. Y. Suen, "An hmm-mlp hybrid model for cursive script recognition," *Pattern Analysis and Applications*, vol. 3, pp. 314–324, 2000. [Online]. Available: <http://dx.doi.org/10.1007/s100440070003>
- [3] J. S. Suri, S. Singh, and L. Reden, "Computer vision and pattern recognition techniques for 2-d and 3-d mr cerebral cortical segmentation: A state-of-the-art review," *JOURNAL OF PATTERN ANALYSIS AND APPLICATIONS*, p. 2002, 2001.
- [4] F. Chang, C.-J. Chen, and C.-J. Lu, "A linear-time component-labeling algorithm using contour tracing technique," *Comput. Vis. Image Underst.*, vol. 93, no. 2, pp. 206–220, Feb. 2004. [Online]. Available: <http://dx.doi.org/10.1016/j.cviu.2003.09.002>
- [5] U. H. Hernandez-Belmonte, V. Ayala-Ramirez, and R. E. Sanchez-Yanez, "A comparative review of two-pass connected component labeling algorithms," in *Proceedings of the 10th international conference on Artificial Intelligence: advances in Soft Computing - Volume Part II*, ser. MICAI'11. Berlin, Heidelberg: Springer-Verlag, 2011, pp. 452–462.
- [6] L. He, Y. Chao, K. Suzuki, and K. Wu, "Fast connected-component labeling," *Pattern Recogn.*, vol. 42, no. 9, pp. 1977–1987, Sep. 2009. [Online]. Available: <http://dx.doi.org/10.1016/j.patcog.2008.10.013>
- [7] R. Haralick, "Some neighborhood operations," in *Real Time Parallel Computing: Image Analysis*, 1981, pp. 11–35.
- [8] C. Fiorio and J. Gustedt, "Two linear time union-find strategies for image processing," *Theor. Comput. Sci.*, vol. 154, no. 2, pp. 165–181, Feb. 1996. [Online]. Available: [http://dx.doi.org/10.1016/0304-3975\(94\)00262-2](http://dx.doi.org/10.1016/0304-3975(94)00262-2)
- [9] F. Chang and C.-J. Chen, "A component-labeling algorithm using contour tracing technique," in *Proceedings of the Seventh International Conference on Document Analysis and Recognition - Volume 2*, ser. ICDAR '03. Washington, DC, USA: IEEE Computer Society, 2003, pp. 741–. [Online]. Available: <http://dl.acm.org/citation.cfm?id=938980.939556>
- [10] H. M. Alnuweiri and V. K. Prasanna, "Parallel architectures and algorithms for image component labeling," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 14, no. 10, pp. 1014–1034, Oct. 1992. [Online]. Available: <http://dx.doi.org/10.1109/34.159904>
- [11] K. A. Hawick, A. Leist, and D. P. Playne, "Parallel graph component labelling with gpus and cuda," *Parallel Comput.*, vol. 36, no. 12, pp. 655–678, Dec. 2010. [Online]. Available: <http://dx.doi.org/10.1016/j.parco.2010.07.002>
- [12] B. B. Ondrej Stava, "Connected component labeling in cuda," in *GPU Computing Gems, Emerald Edition*, W.-M. W. Hwu, Ed. Morgan Kaufmann, 2011, pp. 569–581.
- [13] R. Cole and U. Vishkin, "Faster optimal parallel prefix sums and list ranking," *Inf. Comput.*, vol. 81, no. 3, pp. 334–352, Jun. 1989. [Online]. Available: [http://dx.doi.org/10.1016/0890-5401\(89\)90036-9](http://dx.doi.org/10.1016/0890-5401(89)90036-9)
- [14] —, "Deterministic coin tossing with applications to optimal parallel list ranking," *Inf. Control*, vol. 70, no. 1, pp. 32–53, Jul. 1986. [Online]. Available: [http://dx.doi.org/10.1016/S0019-9958\(86\)80023-7](http://dx.doi.org/10.1016/S0019-9958(86)80023-7)